

2004-2011 RX-8 Bodyshop Manual

FOREWORD

This bodyshop manual is intended for use by technicians of Authorized Mazda Dealers to help them service and repair Mazda vehicles. It can also be useful to owners and operators of Mazda vehicles in performing limited repair and maintenance on Mazda vehicles.

For proper repair and maintenance, a thorough familiarization with this manual is important, and it should always be kept in a handy place for quick and easy reference.

All the contents of this manual, including drawings and specifications, are the latest available at the time of printing.

As modifications affecting repair or maintenance occur, relevant information supplementary to this volume will be made available at Mazda dealers. This manual should be kept up-to-date.

Mazda Motor Corporation reserves the right to alter the specifications and contents of this manual without obligation or advance notice.

All rights reserved. No part of this book may be reproduced or used in any form or by any means, electronic or mechanical including photocopying and recording and the use of any kind of information storage and retrieval system-without permission in writing.

Mazda Motor Corporation
HIROSHIMA, JAPAN

CONTENTS

Title		Section
GENERAL INFORMATION		00
BODY STRUCTURE	CONSTRUCTION	80A
	PANEL REPLACEMENT	80B
	WATER-PROOF AND RUST PREVENTIVE TREATMENT	80C
	DIMENSIONS	80D
	PLASTIC BODY PARTS	80E

APPLICATION:

This manual is applicable to vehicles beginning with the Vehicle Identification Numbers (VIN), shown on the following page.

© 2003 Mazda Motor Corporation
PRINTED IN JAPAN, APRIL 2003
Form No. 3379-1U-03D

VEHICLE IDENTIFICATION NUMBERS (VIN)

JM1	FE172*9#	400001—
JM1	FE174*9#	400001—
JM1	FE17M*9#	400001—
JM1	FE17P*9#	400001—
—	—	—

GENERAL INFORMATION

00
SECTION

00-00

GENERAL INFORMATION . . . 00-00

00-00 GENERAL INFORMATION

HOW TO USE THIS MANUAL	00-00-2	Removal of Associated Parts	00-00-8
Efficient Replacement of		Rough Cutting of Damaged Panel	00-00-9
Body Panels	00-00-2	INSTALLATION PREPARATIONS	00-00-9
Symbols of Panel Replacement	00-00-2	Application of Weld-through Primer . . .	00-00-9
Body Dimensions		Determination of Welding Method	00-00-10
(Flat-plane Dimensions)	00-00-3	Making Holes for CO2 Arc Welding . . .	00-00-10
Body Dimensions		Rough Cutting of New Parts	00-00-10
(Straight-line Dimensions)	00-00-4	EFFICIENT INSTALLATION OF	
Symbols of Body Dimensions	00-00-4	BODY PANELS	00-00-11
SERVICE PRECAUTIONS	00-00-5	Checking Preweld Measurements And	
Arrangement of Workshop	00-00-5	Watching	00-00-11
Vehicle Protection	00-00-5	Welding Notes	00-00-11
Use of Pulling Equipment	00-00-5	Spot Welding Notes	00-00-12
Safety Precautions	00-00-6	Checking Weld Strength.	00-00-13
Prevent Short Circuits	00-00-6	ANTICORROSION, SOUND INSULATION,	
Remove Dangerous Articles	00-00-7	AND VIBRATION INSULATION	00-00-14
EFFICIENT REMOVAL OF		Body Sealing	00-00-14
BODY PANELS	00-00-7	Application of Undercoating	00-00-14
Body Measurements	00-00-7	Application of Rust Inhibitor	00-00-14
Prevention of Body Deformation	00-00-8	Application of Floor Silencer.	00-00-14
Selection of Cut-and-join Locations . . .	00-00-8	ABBREVIATION	00-00-15

GENERAL INFORMATION


HOW TO USE THIS MANUAL

CHU000000001B01

Efficient Replacement of Body Panels

- This section contains information on the body panels in regard to the welding types, number of spot welds, and cut-and-join locations that are necessary for panel removal and installation.
- The type of weld and position are indicated by symbols.
- Some sections have notes concerning the operation being performed. Thoroughly read and understand the notes before carrying out any procedures.

Example



MZZ2010B001

Symbols of Panel Replacement

- The following 6 symbols are used to indicate the type of weld that is used when replacing body panels.

SYMBOL	MEANING	SYMBOL	MEANING
●	Spot welding		Continuous MIG welding (Cut-and-join location)
■	CO ² arc welding (plug welding)	○○○	Braze welding
+	CO ² spot welding	∩	Rough cut location


MZZ2010B002

GENERAL INFORMATION

Body Dimensions (Flat-plane Dimensions)

- Flat-plane dimensions are the dimensions measured by projecting certain reference points onto a plane surface.
- When there are no specific indications, the standard points and dimensions are symmetrical in regard to the center of the vehicle.
- The hypothetical lines may differ according to the vehicle model.

Example




MZZ2010B003

GENERAL INFORMATION

Body Dimensions (Straight-line Dimensions)

- Straight-line dimensions are the actual dimensions between two standard points.
- When there are no specific indications, the standard points and dimensions are symmetrical in regard to the center of the vehicle.

Example



MZZ2010B004

Symbols of Body Dimensions

- The following 8 symbols are used to indicate the standard points.

SYMBOL	MEANING	SYMBOL	MEANING
	Center of circular hole		Panel seam, bead, etc.
	Center elliptical hole		Bolt tip
	Notch		Center of rectangular-shaped hole

MZZ2010B005

SERVICE PRECAUTIONS


CHU000000014B01

Arrangement of Workshop

- Arrangement of the workshop is important for safe and efficient work.

Vehicle Protection


- Use seat covers and floor covers.
- Use heat-resistant protective covers to protect glass areas and seats from heat or sparks during welding.
- Protect items such as moldings, garnishes, and ornaments with tape when welding.



YMU980PA5

Use of Pulling Equipment

- When using pulling equipment, keep away from the pulling area and use safety wires to prevent accidents.




YMU980PA6

GENERAL INFORMATION

Safety Precautions


- Protective head covering and safety shoes should always be worn. Depending upon the nature of the work, gloves, safety glasses, ear protectors, face shield, etc., should also be used.



YMU980PA7

Prevent Short Circuits

- When removing a wiring harness or electrical component, disconnect the negative battery cable.




YMU980PA8

GENERAL INFORMATION

Remove Dangerous Articles

- Remove the fuel tank before using an open flame in that area. Plug connection piping to prevent fuel leakage.




YMU980PA9

EFFICIENT REMOVAL OF BODY PANELS

Body Measurements

- Before removal or rough-cutting, first measure the body at and around the damaged area against the standard reference dimension specifications. If there is deformation, use frame repair equipment to make a rough correction.

CHU000000015B01




YMU980PAA

00-00

GENERAL INFORMATION

Prevention of Body Deformation


- Use a clamp or a jack for removal and reinforce at and around the rough-cutting location to prevent deforming of the body.



YMU980PAB

Selection of Cut-and-join Locations

- For parts where complete replacement is not feasible, careful cutting and joining operations should be followed. If the location to be cut is a flat area where there is no reinforcement, the selected cutting location should be where the welding distortion will be minimal.



YMU980PAC


Removal of Associated Parts

- Protect moldings, garnishes, and ornaments with tape when removing associated parts.

GENERAL INFORMATION

Rough Cutting of Damaged Panel

- Verify that there are no parts (such as pipes, hoses, and wiring harness) nearby or on the opposite side of a panel which could be damaged by heat.
- For cut-and-join areas, allow for an overlap of 30—50 mm {1.18—1.97 in} and then rough-cut the damaged panel.




YMU980PAD

INSTALLATION PREPARATIONS

Application of Weld-through Primer

- For treatment against corrosion, remove the paint, grease, and other material from the portion of new part and body to be welded, and apply weld-through primer.

CHU000000016B01




YMU980PAE

00-00

GENERAL INFORMATION

Determination of Welding Method

- If the total thickness at the area to be welded is 3 mm {0.12 in} or more, use a CO₂ gas shielded-arc welder to make the plug welds.



YMU980PAF


Making Holes for CO₂ Arc Welding

- For places that cannot be spot welded, make a hole for CO₂ arc welding using a punch or drill as follows.

(mm {in})

Panel thickness (ϕ)	Hole diameter (ϕ)
0.60—0.90 {0.02—0.03}	5 {0.19}
0.91—1.20 {0.04—0.05}	6 {0.23}
1.21—1.80 {0.051—0.07}	8 {0.31}
1.81—4.50 {0.071—0.17}	10 {0.39}


- Grind the shaded section indicated in the diagram below and create a hole in the part where the 3—4 plates are put together. Also, weld the plates together tightly so that gaps do not develop.



YMU980PAG

Rough Cutting of New Parts

- For cut-and-join areas, allow for an overlap of 30—50 mm {1.18—1.97 in} with the remaining area on the body side and then rough-cut the new parts.



YMU980PAH


GENERAL INFORMATION

EFFICIENT INSTALLATION OF BODY PANELS

CHU000000017B01

Checking Preweld Measurements And Watching

- Align to the standard reference dimensions, based upon the body dimensions illustration, so that new parts are installed in the correct position.




YMU980PAJ

00-00

Welding Notes

- For the number of weld points, welding should be performed in accordance with the following reference standards.




YMU980PAK

GENERAL INFORMATION


Spot Welding Notes

- The shape of the spot welder tip is $D=(2 \times t)+3$. If the upper panel thickness is different from that of the under panel, adjust to the thinner one.
- Because the weld strength is affected by the shape of the spot welder tip, the optimum condition of the tip should always be maintained.




YMU980PAL

- Spot welds should be made at points other than the originally welded points.
- Before spot welding, make a trial weld using the same material as the body panel to check the weld strength.




YMU980PAM



YMU980PAN


Checking Weld Strength

- Installation locations of the engine, chassis, and seat belts are designated as important safety locations for weld strength. Check weld strength by driving a chisel between the panels at every fourth or fifth weld spot, and every tenth regular weld location.
- Drive the chisel between the panels according to the number of panels as shown below.



YMU980PAP

- To determine weld strength, drive the chisel between the panel and check whether the panels come apart. If the panels come apart, make another weld near the original weld.
- Restore the shape of the checked area.



YMU980PAQ


GENERAL INFORMATION

ANTICORROSION, SOUND INSULATION, AND VIBRATION INSULATION

CHU000000018B01

Body Sealing


- Apply body sealer where necessary.
- For locations where application of body sealer is difficult after installation, apply it before installation.



YMU980PAR

Application of Undercoating


- Apply an undercoat to the required location of the body.



YMU980PAS

Application of Rust Inhibitor


- Apply rust inhibitor (wax, oil, etc.) to the back of the welded areas.



YMU980PAT

Application of Floor Silencer

- Apply floor silencer by heating with an infrared ray lamp.



YMU980PAU

GENERAL INFORMATION

ABBREVIATION

CHU000000011B01

00-00

CM	Control module
Ctr	Center
Fr	Front
HU	Hydraulic unit
LH	Left
M	Metallic
MC	Mica
RH	Right
Rr	Rear

BODY STRUCTURE

09
SECTION

09-80A


CONSTRUCTION09-80A
PANEL REPLACEMENT09-80B
WATER-PROOF AND RUST
PREVENTIVE09-80C

DIMENSIONS 09-80D
PLASTIC BODY PARTS 09-80E

09-80A BODY STRUCTURE [CONSTRUCTION]

BODY COMPONENTS
CONSTRUCTION09-80A-2

CHU098007000B01



CHU0980B094

BODY STRUCTURE [CONSTRUCTION]

x:Applied
-:Not applied

No.	Part Name		High- tension steel	Rust proof steel	Thickness (mm) {in}
1	Hood (*)		-	-	0.90 {0.035}
2	Radiator shroud upper panel		-	x	0.80 {0.031}
3	Radiator shroud side stay		-	x	0.70 {0.028}
4	Radiator shroud lower panel		-	x	0.70 {0.028}
5	Hood rock bracket		-	x	0.80 {0.031}
6	Crossmember No.1	Fr	x	x	0.80 {0.031}
		Rr	x	x	0.70 {0.028}
7	Crossmember No.1 side bracket		x	x	0.80 {0.031}
8	Suspension housing	Upper	x	x	1.40 {0.055}
		Lower	x	x	2.00 {0.079}
9	ABS HU/CM bracket		x	x	1.60 {0.063}
10	Front side frame outer		x	x	1.40 {0.055}
11	Front bumper bracket		x	x	2.60 {0.102}
12	Front side frame inner		x	x	2.00 {0.079}
13	Apron reinforcement upper		x	x	0.90 {0.035}
14	Wheel apron panel		-	x	0.65 {0.026}
15	Front side frame rear reinforcement		x	x	2.00 {0.079}
16	Apron reinforcement lower		x	x	0.75 {0.030}
17	Frame reinforcement		x	x	1.60 {0.063}
18	Dash lower panel		-	x	0.80 {0.031}
19	Dash lower member		x	-	1.60 {0.063}
20	Dash cowl panel		-	x	0.65 {0.026}
21	Cowl upper plate		x	x	1.00 {0.039}
22	Cowl panel		-	x	0.65 {0.026}
23	Front pillar reinforcement		x	-	1.20 {0.047}
24	Side panel inner	Fr	x	-	2.00 {0.079}
		Ctr	x	-	1.40 {0.055}
		Rr	x	-	1.20 {0.047}
25	Hinge reinforcement		x	-	1.60 {0.063}
26	Side panel reinforcement front	Upper	x	-	1.60 {0.063}
		Lower	x	-	1.80 {0.071}
	Side panel reinforcement center		x	-	1.20 {0.047}
	Side panel reinforcement rear	Upper	x	-	1.20 {0.047}
		Lower	x	-	1.00 {0.039}
27	Side sill gusset		-	-	0.90 {0.035}
28	Rear hinge reinforcement	Upper	x	-	1.20 {0.047}
		Lower	x	-	2.30 {0.091}
29	Cowl side reinforcement		x	x	1.20 {0.047}
30	Side panel outer		-	x	0.70 {0.028}
31	Filler box		-	x	0.70 {0.028}
32	Rear fender lower panel		-	x	0.70 {0.028}
33	Rear suspension housing upper		x	-	1.40 {0.055}
34	Package reinforcement		x	-	0.80 {0.031}
35	Roof rail reinforcement		x	-	0.80 {0.031}
36	Rear fender rain rail		-	x	0.70 {0.028}
37	C-pillar reinforcement		x	-	0.90 {0.035}
38	Package gusset		-	-	0.80 {0.031}
39	Rear pillar inner		-	x	0.70 {0.028}
40	Wheel house inner		-	x	0.65 {0.026}
41	Package member front		-	-	0.70 {0.028}
42	Package tray		-	-	0.55 {0.022}

09-80A

BODY STRUCTURE [CONSTRUCTION]

No.	Part Name		High- tension steel	Rust proof steel	Thickness (mm) {in}
43	Package member rear		-	-	0.60 {0.024}
44	Trunk lid panel		-	-	0.75 {0.030}
45	Front header		-	-	0.90 {0.035}
46	Roof panel		-	-	0.85 {0.033}
47	Roof reinforcement		-	-	0.80 {0.031}
48	Rear header		-	-	0.90 {0.035}
49	Front door		-	x	0.70 {0.028}
50	Rear door (*)		-	-	0.90 {0.035}
51	Front fender panel		-	x	0.75 {0.030}
52	Front frame rear upper		x	x	1.60 {0.063}
53	Lower arm bracket		-	x	2.30 {0.091}
54	Front frame rear		x	x	1.60 {0.063}
55	Torque box		-	x	1.20 {0.047}
56	Front B-frame		x	x	1.40 {0.055}
57	Front Floor pan		-	x	0.65 {0.026}
58	Crossmember No.2		x	-	1.40 {0.055}
59	Front floor reinforcement		x	x	1.20 {0.047}
60	Crossmember No.2.5		-	x	1.20 {0.047}
61	Side sill inner		x	x	1.40 {0.055}
62	Side sill reinforcement		x	-	1.80 {0.071}
63	Crossmember No.3	RH	x	x	1.00 {0.039}
		Ctr	-	x	1.60 {0.063}
		LH	x	x	1.00 {0.039}
64	Crossmember No.4		x	x	1.00 {0.039}
65	Crossmember No.5		x	x	0.90 {0.035}
66	Crossmember No.3 front		-	x	1.20 {0.047}
67	Center floor pan		-	x	0.65 {0.026}
68	Tunnel reinforcement rear		-	-	0.90 {0.035}
69	Rear side frame		x	x	1.40 {0.055}
70	Side sill inner rear		x	x	1.40 {0.055}
71	Rear bumper bracket		x	x	1.20 {0.047}
72	Rear side frame rear		x	x	1.40 {0.055}
73	Rear floor pan		-	x	0.65 {0.026}
74	Hook bracket		x	x	1.20 {0.047}
75	Rear side reinforcement		x	x	1.80 {0.071}
76	Rear end member		-	-	0.65 {0.026}
77	Anchor reinforcement		-	x	1.80 {0.071}
78	Rear end panel		-	x	0.60 {0.024}

(*) : Material of hood and rear door are aluminum.

09-80B BODY STRUCTURE [PANEL REPLACEMENT]

RADIATOR SHROUD UPPER PANEL	
REMOVAL	09-80B-2
RADIATOR SHROUD UPPER PANEL	
INSTALLATION	09-80B-2
RADIATOR SHROUD LOWER PANEL	
REMOVAL	09-80B-3
RADIATOR SHROUD LOWER PANEL	
INSTALLATION	09-80B-3
FRONT BUMPER BRACKET	
REMOVAL	09-80B-4
FRONT BUMPER BRACKET	
INSTALLATION	09-80B-4
ABS HU/CM BRACKET REMOVAL	
09-80B-5	
ABS HU/CM BRACKET	
INSTALLATION	09-80B-5
CROSSMEMBER No.1 REMOVAL	
09-80B-5	
CROSSMEMBER No.1	
INSTALLATION	09-80B-7
COWL SIDE REINFORCEMENT	
REMOVAL	09-80B-7
COWL SIDE REINFORCEMENT	
INSTALLATION	09-80B-9
APRON REINFORCEMENT UPPER	
REMOVAL	09-80B-9
APRON REINFORCEMENT UPPER	
INSTALLATION	09-80B-11
APRON REINFORCEMENT LOWER	
REMOVAL	09-80B-12
APRON REINFORCEMENT LOWER	
INSTALLATION	09-80B-13
WHEEL APRON PANEL COMPONENT	
REMOVAL	09-80B-14
WHEEL APRON PANEL COMPONENT	
INSTALLATION	09-80B-15
FRONT SIDE FRAME REAR	
REINFORCEMENT REMOVAL	09-80B-15
FRONT SIDE FRAME REAR	
REINFORCEMENT INSTALLATION...	09-80B-17
FRONT SIDE FRAME REMOVAL	
09-80B-17	
FRONT SIDE FRAME	
INSTALLATION	09-80B-19
FRONT SIDE FRAME OUTER	
REMOVAL	09-80B-20
FRONT SIDE FRAME OUTER	
INSTALLATION	09-80B-21
FRONT SIDE FRAME (PARTIAL CUTTING)	
REMOVAL	09-80B-22


FRONT SIDE FRAME (PARTIAL CUTTING)	
INSTALLATION	09-80B-23
TORQUE BOX REMOVAL	
09-80B-23	
TORQUE BOX INSTALLATION	
09-80B-25	
FRONT FRAME REAR UPPER	
REMOVAL	09-80B-25
FRONT FRAME REAR UPPER	
INSTALLATION	09-80B-27
FRONT FRAME REAR REMOVAL	
09-80B-28	
FRONT FRAME REAR	
INSTALLATION	09-80B-29
FRAME REINFORCEMENT REMOVAL ..	
09-80B-29	
FRAME REINFORCEMENT	
INSTALLATION	09-80B-31
COWL UPPER PLATE REMOVAL	
09-80B-31	
COWL UPPER PLATE	
INSTALLATION	09-80B-33
FRONT PILLAR REMOVAL	
09-80B-33	
FRONT PILLAR INSTALLATION	
09-80B-36	
REAR FENDER PANEL REMOVAL	
09-80B-37	
REAR FENDER PANEL	
INSTALLATION	09-80B-40
REAR FENDER LOWER PANEL	
REMOVAL	09-80B-42
REAR FENDER LOWER PANEL	
INSTALLATION	09-80B-43
SIDE SILL PANEL FRONT	
REMOVAL	09-80B-43
SIDE SILL PANEL FRONT	
INSTALLATION	09-80B-45
SIDE SILL PANEL REMOVAL	
09-80B-46	
SIDE SILL PANEL INSTALLATION	
09-80B-47	
[Drill Hole Install for Rear Deflector] ..	
09-80B-48	
REAR END PANEL REMOVAL	
09-80B-49	
REAR END PANEL INSTALLATION	
09-80B-49	
REAR FENDER RAIN RAIL AND	
CORNER PLATE REMOVAL	09-80B-50
REAR FENDER RAIN RAIL AND	
CORNER PLATE INSTALLATION	09-80B-51
REAR FLOOR PAN REMOVAL	
09-80B-51	
REAR FLOOR PAN INSTALLATION	
09-80B-53	
REAR SIDE FRAME (PARTIAL CUTTING)	
REMOVAL	09-80B-53
REAR SIDE FRAME (PARTIAL CUTTING)	
INSTALLATION	09-80B-55
ROOF PANEL REMOVAL	
09-80B-55	
ROOF PANEL INSTALLATION	
09-80B-57	

09-80B

RADIATOR SHROUD UPPER PANEL REMOVAL

CHU098053100B01

1. Remove the radiator shroud upper panel.




CHU0980B036

RADIATOR SHROUD UPPER PANEL INSTALLATION

CHU098053100B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.



CHU0980B037

BODY STRUCTURE [PANEL REPLACEMENT]


RADIATOR SHROUD LOWER PANEL REMOVAL

CHU098053100B03

1. Remove the radiator shroud lower panel.

Note

- When removing the radiator shroud side stay and the hood lock bracket separately, drill the 14 weld locations indicated by (A) and the seven weld locations indicated by (B).



CHU0980B038


RADIATOR SHROUD LOWER PANEL INSTALLATION

CHU098053100B04

1. Weld the 14 locations indicated by (A), then temporarily install the condenser bracket and oil cooler bracket.
2. When installing new parts, position each part so that the section measurement aligns with the body dimension.
3. Drill holes for plug welds before installing new parts.
4. Weld the remaining weld locations and install the radiator shroud lower panel.
5. After temporarily installing new parts, make sure the related parts fit properly.

Note

- When replacing the radiator shroud side stay and the hood lock bracket separately, weld the 27 locations indicated by (B).




CHU0980B039

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT BUMPER BRACKET REMOVAL

CHU098053896B01

1. Remove the front bumper bracket.




CHU0980B032

FRONT BUMPER BRACKET INSTALLATION

CHU098053896B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.




CHU0980B033

BODY STRUCTURE [PANEL REPLACEMENT]

ABS HU/CM BRACKET REMOVAL

CHU098053318B01

1. Remove the ABS HU/CM bracket.




09-80B

CHU0980B034

ABS HU/CM BRACKET INSTALLATION

CHU098053318B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.




CHU0980B035

BODY STRUCTURE [PANEL REPLACEMENT]

CROSSMEMBER NO.1 REMOVAL

CHU098053160B01

1. Remove the crossmember No.1.
2. Remove the crossmember No.1 side bracket.



CHU0980B040


BODY STRUCTURE [PANEL REPLACEMENT]

CROSSMEMBER NO.1 INSTALLATION



CHU098053160B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.


09-80B



CROSSMEMBER No.1 SIDE BRACKET



CROSSMEMBER No.1




CHU0980B041

BODY STRUCTURE [PANEL REPLACEMENT]

COWL SIDE REINFORCEMENT REMOVAL

CHU098053290B01

1. Drill the three weld locations indicated by (A) and remove the fender bracket.
2. Drill the 47 weld locations indicated by (B) and remove the cowl side reinforcement.
3. Drill the five weld locations indicated by (C) and remove the cowl side reinforcement inner.




CHU0980B042

BODY STRUCTURE [PANEL REPLACEMENT]

COWL SIDE REINFORCEMENT INSTALLATION

CHU098053290B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. Weld the 18 locations indicated by (A), then temporarily installing the cowl side reinforcement inner and cowl side reinforcement.
4. After temporarily installing new parts, make sure the related parts fit properly.



09-80B


CHU0980B043

BODY STRUCTURE [PANEL REPLACEMENT]

APRON REINFORCEMENT UPPER REMOVAL

CHU098053260B01

1. Remove the apron reinforcement upper.




CHU0980B044

BODY STRUCTURE [PANEL REPLACEMENT]

APRON REINFORCEMENT UPPER INSTALLATION

CHU098053260B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.



CHU0980B045



09-80B

BODY STRUCTURE [PANEL REPLACEMENT]

APRON REINFORCEMENT LOWER REMOVAL

CHU098053260B03

1. Remove the apron reinforcement lower.





CHU0980B046

BODY STRUCTURE [PANEL REPLACEMENT]

APRON REINFORCEMENT LOWER INSTALLATION

CHU098053260B04

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.



09-80B

CHU0980B047

BODY STRUCTURE [PANEL REPLACEMENT]


WHEEL APRON PANEL COMPONENT REMOVAL

CHU098053210B01

1. Drill the 18 weld locations indicated by (A) and 15 locations (B), then remove the wheel apron panel component.

Note

- When removing the wheel apron panel front and the wheel apron panel rear separately, drill the 18 weld locations indicated by (A) and the three weld locations by (C).



CHU0980B048

BODY STRUCTURE [PANEL REPLACEMENT]

WHEEL APRON PANEL COMPONENT INSTALLATION


CHU098053210B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.

Note

- When replacing the wheel apron panel front and the wheel apron panel rear separately, weld 16 locations indicated by (A).
4. Plug the six weld location indicated by (B) when installing the apron reinforcement upper.

09-80B




CHU0980B049

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT SIDE FRAME REAR REINFORCEMENT REMOVAL

CHU098053396B01

1. Remove the front side frame rear reinforcement.




CHU0980B050

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT SIDE FRAME REAR REINFORCEMENT INSTALLATION

CHU098053396B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.



09-80B


CHU0980B051

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT SIDE FRAME REMOVAL

CHU098053300B01

1. Remove the front side frame.






CHU0980B052

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT SIDE FRAME INSTALLATION

CHU098053300B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.



CHU0980B053


09-80B

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT SIDE FRAME OUTER REMOVAL

CHU098053300B03

1. To facilitate removal of the front side frame outer, drill the five weld locations indicated by (A) and bend the wheel apron panel front upward.
2. Drill the one weld locations indicated by (B) and 15 weld locations (C) then remove the front side frame outer.




CHU0980B062

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT SIDE FRAME OUTER INSTALLATION

CHU098053300B04

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. Weld the one locations indicated by (A), then temporarily installing the inner and outer.
4. After temporarily installing new parts, make sure the related parts fit properly.



CHU0980B063


09-80B

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT SIDE FRAME (PARTIAL CUTTING) REMOVAL

CHU098053300B05

1. Rough cut and remove the damaged part of the front side frame.



CHU0980B056

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT SIDE FRAME (PARTIAL CUTTING) INSTALLATION


CHU098053300B06

1. Cut the new and old parts at the cut-and-join location, and bevel the parts.
2. To cut-and-join the new part, cut at the locations indicated in the figure below and bevel the cut-and-join locations of the new parts.
3. When installing the new parts, trial-fit them to the body, and position each part so that the each section alignment matches the body dimensions.
4. After temporarily installing new parts, make sure the related parts fit properly.

Caution

- The cut-and-joint area indicates the maximum size range of the installation position.

09-80B




CHU0980B057

BODY STRUCTURE [PANEL REPLACEMENT]

TORQUE BOX REMOVAL

CHU098053381B01

1. Remove the torque box.




CHU0980B060

BODY STRUCTURE [PANEL REPLACEMENT]

TORQUE BOX INSTALLATION

CHU098053381B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.



09-80B


CHU0980B061

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT FRAME REAR UPPER REMOVAL

CHU098053390B01

1. Drill the 16 weld locations indicated by (A) and remove the lower arm bracket.
2. Drill the remaining weld locations and remove the front frame rear upper.







CHU0980B064

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT FRAME REAR UPPER INSTALLATION

CHU098053390B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. Weld the 18 locations indicated by (A) and install the front frame rear upper.
4. After temporarily installing new parts, make sure the related parts fit properly.
5. Plug the one weld location indicated by (B) when installing the torque box.



CHU0980B065


09-80B

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT FRAME REAR REMOVAL

CHU098053390B03

1. Remove the front frame rear.





CHU0980B068

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT FRAME REAR INSTALLATION

CHU098053390B04

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.



CHU0980B069

09-80B

BODY STRUCTURE [PANEL REPLACEMENT]


FRAME REINFORCEMENT REMOVAL

CHU098053342B01

1. Remove the frame reinforcement.

Note

- When removing the frame reinforcement inner and the frame reinforcement outer separately, drill the five weld locations indicated by (A).



CHU0980B066

BODY STRUCTURE [PANEL REPLACEMENT]


FRAME REINFORCEMENT INSTALLATION

CHU098053342B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.

Note

- When replacing the frame reinforcement inner and the frame reinforcement outer separately, weld six weld locations indicated by (A).



09-80B

CHU0980B067

BODY STRUCTURE [PANEL REPLACEMENT]

COWL UPPER PLATE REMOVAL



CHU098053580B01

1. Drill the four weld locations indicated by (A), from the room side.
2. Remove the cowl upper plate.




Caution

- Be careful not to damage the windshield when drilling the location indicated by (B).

DRIVER'S SIDE



PASSENGER'S SIDE



CHU0980B058



BODY STRUCTURE [PANEL REPLACEMENT]

COWL UPPER PLATE INSTALLATION




CHU098053580B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.

DRIVER'S SIDE



PASSENGER'S SIDE



CHU0980B059

09-80B

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT PILLAR REMOVAL

CHU098074090B01

1. Rough cut area (A), drill the 42 weld locations indicated by (B), then remove the lower part of the front pillar outer.

Caution


- Avoid cutting with a blowtorch or similar tools as the insulator (shaded area) is flammable.

2. Rough cut area (C), drill the 55 weld locations indicated by (D) and one location (E), then remove the front pillar outer and reinforcement.

Note

- For weld location (E), partially bend back the cowl upper plate before drilling.


3. Rough cut area (F), drill the 11 weld locations indicated by (G), then remove the front pillar inner.



CHU0980B070

BODY STRUCTURE [PANEL REPLACEMENT]

09-80B



CHU0980B071

BODY STRUCTURE [PANEL REPLACEMENT]

FRONT PILLAR INSTALLATION


CHU098074090B02

1. When joining the new and old parts, temporarily install and fit the new part in position, measure each dimension according to the body dimension, then adjust the position to align it to the standard dimensions.
2. Drill holes for plug welds before installing new parts.

Note



- In areas where the outer, reinforcement, inner, etc. are in 3-4 layers, drill holes for plug welds in all but the innermost panel.

3. After temporarily installing new parts, make sure the related parts fit properly.





CHU0980B073

BODY STRUCTURE [PANEL REPLACEMENT]



09-80B



CHU0980B072

BODY STRUCTURE [PANEL REPLACEMENT]

REAR FENDER PANEL REMOVAL

CHU098074100B01


Caution

- Avoid cutting with a blowtorch or similar tools as the insulator (shaded area) is flammable.

Note



- For weld location (A), partially bend back the rear end panel before drilling.

1. The rear fender panel and the rear pillar inner are joined with glue at the wheel arch line. Use a chisel or other to separate the rear fender panel from the rear pillar inner, then remove the rear fender panel.



CHU0980B074

BODY STRUCTURE [PANEL REPLACEMENT]



09-80B


CHU0980B075

BODY STRUCTURE [PANEL REPLACEMENT]


CHU098074100B02

REAR FENDER PANEL INSTALLATION


1. When joining the new and old parts, temporarily install and fit the new part in position, measure each dimension according to the body dimension, then adjust the position to align it to the standard dimensions.
2. Drill holes for plug welds before installing new parts.
3. Weld in 24 locations indicated by (A), then temporarily installing the rear pillar hinge reinforcement.
4. Plug the one weld location indicated by (B), when installing the rear end panel.
5. After temporarily installing new parts, make sure the related parts fit properly.



REAR PILLAR HINGE REINFORCEMENT




SIDE SILL REAR REINFORCEMENT



CHU0980B093

BODY STRUCTURE [PANEL REPLACEMENT]

09-80B




CHU0980B092

BODY STRUCTURE [PANEL REPLACEMENT]

REAR FENDER LOWER PANEL REMOVAL

CHU098074100B03

1. Remove the rear fender lower panel.




CHU0980B076

BODY STRUCTURE [PANEL REPLACEMENT]

REAR FENDER LOWER PANEL INSTALLATION

CHU098074100B04

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.



09-80B


CHU0980B077

BODY STRUCTURE [PANEL REPLACEMENT]

SIDE SILL PANEL FRONT REMOVAL

CHU098070270B01

1. Rough cut area (A) and drill the 39 weld locations indicated by (B), then remove the side sill outer.
2. Rough cut area (C) and drill the 11 weld locations indicated by (D), then remove the side sill reinforcement.
3. Rough cut area (E) and remove the side sill gusset.



CHU0980B086

BODY STRUCTURE [PANEL REPLACEMENT]

SIDE SILL PANEL FRONT INSTALLATION

CHU098070270B02


1. When joining the new and old parts, temporarily install and fit the new part in position, measure each dimension according to the body dimension, then adjust the position to align it to the standard dimensions.

Caution

- When cutting and joining the side sill reinforcement, make sure not to damage or scratch the side sill gusset.

2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.

09-80B



CHU0980B087

BODY STRUCTURE [PANEL REPLACEMENT]

SIDE SILL PANEL REMOVAL


CHU098070270B03

1. Rough cut area (A) and drill the 110 weld locations indicated by (B), then remove the side sill outer.

Caution

- Avoid cutting with a blowtorch or similar tools as the insulator (shaded area) is flammable.

2. Rough cut area (C) and drill the 40 weld locations indicated by (D), then remove the side sill reinforcement.
3. Remove the side sill rear reinforcement.




CHU0980B078

SIDE SILL PANEL INSTALLATION

CHU098070270B04

1. When joining the new and old parts, temporarily install and fit the new part in position, measure each dimension according to the body dimension, then adjust the position to align it to the standard dimensions.
2. Drill holes for plug welds before installing new parts.
3. Weld the six locations indicated by (A) and install the side sill rear reinforcement.
4. Weld the 28 locations indicated by (B), then temporarily install the side sill gusset.
5. Weld the 12 locations indicated by (C) and install the side sill reinforcement.
6. Weld the 110 locations indicated by (D) and install the side sill outer.
7. After temporarily installing new parts, make sure the related parts fit properly.

09-80B



CHU0980B079

Drill Hole Install for Rear Deflector


1. Cut out the templates along the cut lines.
2. Face the printed side of the templates to the rear deflector, align two sides of the templates, and affix them to the rear deflector using double-sided adhesive tape.

Caution

- Affix double-sided adhesive tape on the printed side of the templates.


Note

- Paper type double-sided adhesive tape is recommended.



ar8uub00000073

3. Align the rear deflector with the installation position with no clearance with the body, and temporarily fix using a rivet.




ar8uub00000074

4. Align the rear deflector bottom surface with the body, press it so that there is no clearance with the body.

Caution

- Be careful of the alignment of the rear deflector with the body and verify that it is firmly attached to the lower surface of the rear deflector with its height equal with the body from front to back.



ar8uub00000075

2004 Mazda RX-8 Bodyshop Manual(3379-1U-03D)
BODY STRUCTURE [PANEL REPLACEMENT]

5. Place the templates along the bodyline and affix them using tape.
6. Remove the fastener and remove the rear deflector with the templates affixed to the body.

Caution

- When removing the rear deflector, be careful that the templates do not slip or become ripped.

7. Place the templates along the bodyline and punch holes through the center of the templates.

Caution

- Punch holes through the center of the templates with the templates affixed to the body.


8. Remove the templates.

9. Wrap packing tape around the drill bit.

Note


- To prevent damage and overdrilling.

10. With the drill bit pointed perpendicular to the body, drill a hole gradually using a $\phi 3$ mm {0.1in}, $\phi 6$ mm {0.2in}, then $\phi 10$ mm {0.39in} drill bit.




ar8uub00000076


09-08B



am2zzb00000010




am2zzb00000001



am2zzb00000017

2004 Mazda RX-8 Bodyshop Manual(3379-1U-03D)
BODY STRUCTURE [PANEL REPLACEMENT]

11. Grind the drilled hole to remove any metal burrs with a round file to finish the surface.




am2zzb0000010

12. Wipe off dirt from the rear deflector installation surface on the body using a clean rag dampened with isopropyl alcohol.
13. Apply sealant for rust protection.
14. Apply touch-up paint.

Caution

- Make sure rust protection is performed properly.






ar8uub0000077

Template

TEMPLATE

LH

RH



09-08B


ar8uub00000078

**THIS PAGE INTENTIONALLY
LEFT BLANK**

REAR END PANEL REMOVAL

CHU098070750B01

1. Remove the rear end panel.




CHU0980B080

09-80B

REAR END PANEL INSTALLATION

CHU098070750B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.



CHU0980B081


REAR FENDER RAIN RAIL AND CORNER PLATE REMOVAL

CHU098070440B01

1. Remove the rear fender rain rail and corner plate.


Note

- When removing the rear fender rain rail and the corner plate separately, drill three weld locations indicated by (A).



REAR FENDER RAIN RAIL

CORNER PLATE



CHU0980B082

BODY STRUCTURE [PANEL REPLACEMENT]


REAR FENDER RAIN RAIL AND CORNER PLATE INSTALLATION

CHU098070440B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.


Note

- When replacing the rear fender rain rail and the corner plate separately, weld three locations indicated by (A).



REAR FENDER RAIN RAIL

CORNER PLATE



09-80B


CHU0980B083

BODY STRUCTURE [PANEL REPLACEMENT]

REAR FLOOR PAN REMOVAL

CHU098053750B01

1. Remove the rear floor pan.




CHU0980B084

BODY STRUCTURE [PANEL REPLACEMENT]

REAR FLOOR PAN INSTALLATION

CHU098053750B02

1. Drill holes for plug welds before installing new parts.
2. After temporarily installing new parts, make sure the related parts fit properly.



09-80B


CHU0980B085

BODY STRUCTURE [PANEL REPLACEMENT]

REAR SIDE FRAME (PARTIAL CUTTING) REMOVAL

CHU098053810B01

1. Rough cut and remove the damaged part of the rear side frame.



CHU0980B088

BODY STRUCTURE [PANEL REPLACEMENT]

REAR SIDE FRAME (PARTIAL CUTTING) INSTALLATION


CHU098053810B02

1. Cut the new and old parts at the cut-and-join location, and bevel the parts.
2. To cut-and-join the new part, cut at the locations indicated in the figure below and bevel the cut-and-join locations of the new parts.
3. When installing the new parts, trial-fit them to the body, and position each part so that the each section alignment matches the body dimensions.
4. After temporarily installing new parts, make sure the related parts fit properly.

Caution

- The cut-and-join area indicates the maximum size range of the installation position.

09-80B




CHU0980B089

BODY STRUCTURE [PANEL REPLACEMENT]

ROOF PANEL REMOVAL

CHU098070600B01

1. Remove the roof panel.




CHU0980B090

BODY STRUCTURE [PANEL REPLACEMENT]

ROOF PANEL INSTALLATION

CHU098070600B02

1. When installing new parts, position each part so that the section measurement aligns with the body dimension.
2. Drill holes for plug welds before installing new parts.
3. After temporarily installing new parts, make sure the related parts fit properly.



CHU0980B091

09-80B

09-80C BODY STRUCTURE [WATER-PROOF AND RUST PREVENTIVE TREATMENT]


BODY SEALING 09-80C-1
UNDER COATING 09-80C-4

[CHIPPING-RESISTANT COATING] 09-80C-4
RUST PREVENTIVE TREATMENT 09-80C-5

BODY SEALING


CHU098007000B02

Sealant is applied to the parts where the panels meet and to the hemmed parts of the door panel and hood panel to provide water proofing and rust proofing.




09-80C

CHU0980B024




CHU0980B025


HOOD



DOOR



TRUNK LID



09-80C


CHU0980B026

2004 Mazda RX-8 BodyShop Manual(3379-1U-03D)
BODY STRUCTURE [WATER-PROOF AND RUST PREVENTIVE TREATMENT]

UNDER COATING

CHU098007000B03

The shaded areas indicated under body locations that are undercoated to prevent noise and rusting.




CHU0980B227

CHIPPING-RESISTANT COATING

CHU098007000B04

The coating locations are indicated by the shaded areas.




CHU0980B228

BODY STRUCTURE [WATER-PROOF AND RUST PREVENTIVE TREATMENT]

UNDER COATING

CHU098007000B03

The shaded areas indicate under body locations that are undercoated to prevent noise and rusting.




CHU0980B027

PCV PAINTING

CHU098007000B04

The coating locations are indicated by the shaded areas.




CHU0980B028

BODY STRUCTURE [WATER-PROOF AND RUST PREVENTIVE TREATMENT]




RUST PREVENTIVE TREATMENT

CHU098007000B05



HOOD HINGE



DOOR



TRUNK LID



09-80C

CHU0980B029

09-80D BODY STRUCTURE [DIMENSIONS]


UNDERBODY FLAT-PLANE		CABIN SIDE FRAME STRAIGHT-LINE	
DIMENSIONS	09-80D-2	DIMENSIONS (2)	09-80D-8
UNDERBODY STRAIGHT-LINE		ROOM STRAIGHT-LINE	
DIMENSIONS	09-80D-3	DIMENSIONS (1)	09-80D-9
FRONT BODY STRAIGHT-LINE		ROOM STRAIGHT-LINE	
DIMENSIONS (1).....	09-80D-4	DIMENSIONS (2)	09-80D-10
FRONT BODY STRAIGHT-LINE		ROOM STRAIGHT-LINE	
DIMENSIONS (2).....	09-80D-5	DIMENSIONS (3)	09-80D-11
FRONT BODY STRAIGHT-LINE		REAR BODY STRAIGHT-LINE	
DIMENSIONS (3).....	09-80D-6	DIMENSIONS	09-80D-12
CABIN SIDE FRAME STRAIGHT-LINE			
DIMENSIONS (1).....	09-80D-7		

09-80D

BODY STRUCTURE [DIMENSIONS]

UNDERBODY FLAT-PLANE DIMENSIONS

CHU098053010B01



CHU0980B005


Point symbol	Designation	Hole diameter or bolt or nut size mm {in}
A	Front side frame standard hole	ø9.8 {0.39}
B	Crossmember No.1 standard hole	ø7 {0.28}
C	Front crossmember mounting bolt	M14 {0.55}
D	Front suspension mounting block	ø44 {1.73}
E	Front crossmember mounting bolt	M14 {0.55}
F	Front frame rear standard hole	ø16 {0.63}
G	Front frame rear standard hole	16 × 20 {0.63 × 0.79}
H	Front B frame standard hole	M14 {0.55}

Point symbol	Designation	Hole diameter or bolt or nut size mm {in}
I	Front B frame standard hole	ø20 {0.79}
J	Rear side frame standard hole	ø16 {0.63}
K	Rear crossmember mounting bolt	M14 {0.55}
L	Rear crossmember mounting bolt	M14 {0.55}
M	Rear suspension mounting block	ø97 {3.82}
N	Rear crossmember mounting bolt	M14 {0.55}
O	Bumper bracket standard hole	14 × 10 {0.55 × 0.39}

BODY STRUCTURE [DIMENSIONS]


UNDERBODY STRAIGHT-LINE DIMENSIONS

CHU098053010B02



CHU0980B006

09-80D



CHU0980B007


Measured location	Dimensions mm {in}
1	254 {10.00}
2	827 {32.56}
3	184 {7.24}
4	808 {31.81}
5	RH:116 {4.57}, LH:115 {4.53}
6	804 {31.65}
7	RH:855 {33.66}, LH:857 {33.74}
8	RH:294 {11.57}, LH:299 {11.77}
9	1,157 {45.55}
10	833 {32.80}
11	330 {12.99}
12	868 {34.17}
13	570 {22.44}
14	979 {38.54}
15	471 {18.54}

Measured location	Dimensions mm {in}
16	RH:923 {36.34}, LH:927 {36.50}
17	RH:307 {12.09}, LH:310 {12.20}
18	RH:1,585 {62.40}, LH:1,587 {62.48}
19	1,367 {53.82}
20	RH:1,042 {41.02}, LH:1,039 {40.91}
21	545 {21.46}
22	1,236 {48.66}
23	339 {13.35}
24	968 {38.11}
25	243 {9.57}
26	861 {33.90}
27	438 {17.24}
28	937 {36.89}
29	1,799 {70.83}
30	1,485 {58.46}


BODY STRUCTURE [DIMENSIONS]

FRONT BODY STRAIGHT-LINE DIMENSIONS (1)

CHU098053020B01



CHU0980B008



CHU0980B009

Measured location	Dimensions mm {in}
1	954 {37.56}
2	1,350 {53.15}
3	676 {26.61}
4	1,430 {56.30}
5	1,406 {55.35}
6	1,604 {63.15}
7	675 {26.57}
8	1,214 {47.80}
9	584 {22.99}
10	1,450 {57.09}


Measured location	Dimensions mm {in}
11	1,254 {49.37}
12	358 {14.09}
13	1,313 {51.69}
14	903 {35.55}
15	1,266 {49.84}
16	1,176 {46.30}
17	314 {12.36}
18	1,010 {39.76}
19	783 {30.83}

BODY STRUCTURE [DIMENSIONS]


FRONT BODY STRAIGHT-LINE DIMENSIONS (2)

CHU098053020B02

09-80D



CHU0980B010



CHU0980B011


Measured location	Dimensions mm {in}
1	760 {29.92}
2	696 {27.40}
3	585 {23.03}
4	882 {34.72}
5	868 {34.17}

Measured location	Dimensions mm {in}
6	983 {38.70}
7	512 {20.16}
8	758 {29.84}
9	816 {32.13}
10	796 {31.34}


BODY STRUCTURE [DIMENSIONS]

FRONT BODY STRAIGHT-LINE DIMENSIONS (3)

CHU098053020B03



CHU0980B012



CHU0980B013


Measured location	Dimensions mm {in}
1	1,550 {61.02}
2	1,554 {61.18}
3	1,547 {60.91}
4	868 {34.17}
5	879 {34.61}

Measured location	Dimensions mm {in}
6	868 {34.17}
7	405 {15.94}
8	461 {18.15}
9	356 {14.02}
10	384 {15.12}


BODY STRUCTURE [DIMENSIONS]

CABIN SIDE FRAME STRAIGHT-LINE DIMENSIONS (1)

CHU098070010B01



CHU0980B014



CHU0980B015


Measured location	Dimensions mm {in}
1	785 {30.91}
2	840 {33.07}
3	1,036 {40.79}
4	1,015 {39.96}
5	901 {35.47}
6	1,686 {66.38}
7	1,706 {67.17}
8	1,653 {65.08}
9	1,230 {48.43}
10	484 {19.06}

Measured location	Dimensions mm {in}
11	1,103 {43.43}
12	1,809 {71.22}
13	1,765 {69.49}
14	1,667 {65.63}
15	1,162 {45.75}
16	993 {39.09}
17	1,039 {40.91}
18	788 {31.02}
19	592 {23.31}


BODY STRUCTURE [DIMENSIONS]

CABIN SIDE FRAME STRAIGHT-LINE DIMENSIONS (2)

CHU098070010B02



CHU0980B016



CHU0980B017


Measured location	Dimensions mm {in}
1	1,217 {47.91}
2	1,310 {51.57}
3	1,315 {51.77}
4	1,045 {41.14}
5	681 {26.81}
6	964 {37.95}
7	1,571 {61.85}

Measured location	Dimensions mm {in}
8	1,492 {58.74}
9	1,376 {54.17}
10	403 {15.87}
11	1,016 {40.00}
12	631 {24.84}
13	1,080 {42.52}

BODY STRUCTURE [DIMENSIONS]


ROOM STRAIGHT-LINE DIMENSIONS (1)

CHU098070001B01



CHU0980B018

09-80D



CHU0980B019


Measured location	Dimensions mm {in}
1	RH:892 {35.12}, LH:839 {33.03}
2	RH:800 {31.50}, LH:734 {28.90}
3	RH:788 {31.02}, LH:711 {27.99}
4	RH:1,160 {45.67}, LH:1,125 {44.29}
5	RH:1,367 {53.82}, LH:1,337 {52.64}

Measured location	Dimensions mm {in}
6	RH:1,618 {63.70}, LH:1,593 {62.72}
7	RH:1,886 {74.25}, LH:1,862 {73.31}
8	RH:1,742 {68.58}, LH:1,710 {67.32}
9	RH:1,529 {60.20}, LH:1,490 {58.66}
K-K'	1,512 {59.53}


BODY STRUCTURE [DIMENSIONS]

ROOM STRAIGHT-LINE DIMENSIONS (2)

CHU098070001B02



CHU0980B020



CHU0980B021


Measured location	Dimensions mm {in}
1	1,115 {43.90}
2	1,265 {49.80}
3	1,350 {53.15}
4	978 {38.50}
5	951 {37.44}
6	1,015 {39.96}

Measured location	Dimensions mm {in}
7	1,144 {45.04}
8	1,007 {39.65}
9	822 {32.36}
F-F'	1,001 {39.41}
K-K'	1,568 {61.73}


BODY STRUCTURE [DIMENSIONS]

ROOM STRAIGHT-LINE DIMENSIONS (3)

CHU098070001B03



CHU0980B030



CHU0980B031


Measured location	Dimensions mm {in}
1	1,524 {60.00}
2	1,737 {68.39}
3	1,858 {73.15}
4	1,225 {48.23}
5	1,049 {41.30}

Measured location	Dimensions mm {in}
6	921 {36.26}
7	862 {33.94}
8	794 {31.26}
9	752 {29.61}
K-K'	1,546 {60.87}


BODY STRUCTURE [DIMENSIONS]

REAR BODY STRAIGHT-LINE DIMENSIONS

CHU098070002B01



CHU0980B022



CHU0980B023

Measured location	Dimensions mm {in}
1	885 {34.84}
2	1,120 {44.09}
3	592 {23.31}
4	1,022 {40.24}
5	849 {33.43}
6	491 {19.33}
7	470 {18.50}
8	1,268 {49.92}

Measured location	Dimensions mm {in}
9	1,253 {49.33}
10	198 {7.80}
11	RH:968 {38.11}, LH:952 {37.48}
12	RH:576 {22.68}, LH:574 {22.60}
13	1,207 {47.52}
14	RH:873 {34.37}, LH:853 {33.58}
15	RH:433 {17.05}, LH:427 {16.81}
16	467 {18.39}

09-80E BODY STRUCTURE [PLASTIC BODY PARTS]

PLASTIC PARTS HEAT RESISTING
TEMPERATURE 09-80E-1
REPAIRABLE RANGE OF
POLYPROPYLENE BUMPERS 09-80E-2

Repairable Bumpers 09-80E-2
POLYPROPYLENE BUMPER REPAIR .. 09-80E-3
PROCEDURE 09-80E-4

PLASTIC PARTS HEAT RESISTING TEMPERATURE

CHU098050000B01

Part Name		Code	Material Name	Heat resisting Temperature°C {°F}
WINDSHIELD MOULDING		PVC	POLYVINYLCHLORIDE	95 {203}
COWL GRILLE		PP	POLYPROPYLENE	100 {212}
FRONT COMBINATION LIGHT	LENS	PC	POLYCARBONATE	130 {266}
	HOUSING	PP	POLYPROPYLENE	95 {203}
FRONT BUMPER		PP	POLYPROPYLENE	100 {212}
FRONT SIDE MARKER LIGHT	LENS	PMMA	ACRYLIC	75 {167}
	HOUSING	ASS	ASS	80 {176}
OUTER HANDLE	HANDLE BASE	PC-PET	POLYCARBONATE-PET	80 {176}
	HANDLE LEVER	PC-PBT	POLYCARBONATE-PBT	80 {176}
OUTSIDE MIRROR		ABS	ABS	90 {194}
REAR COMBINATION LIGHT	LENS	PMMA	ACRYLIC	80 {176}
	HOUSING	AES	AES	70 {158}
REAR BUMPER		PP	POLYPROPYLENE	100 {212}
HIGH-MOUNT BRAKE LIGHT		PC	POLYCARBONATE	100 {212}
ROOF MOULDING		PVC	POLYVINYLCHLORIDE	95 {203}
BELTLINE MOLDING		PVC	POLYVINYLCHLORIDE	95 {203}
FENDER GRILLE		PP	POLYPROPYLENE	100 {212}

09-80E

Note

- The application of temperatures higher than heat resisting temperatures may result in part deformation.

BODY STRUCTURE [PLASTIC BODY PARTS]


REPAIRABLE RANGE OF POLYPROPYLENE BUMPERS

CHU098050010B01

The three types of damaged bumpers shown below are considered repairable. Although a bumper which has been damaged greater than this could also be repaired, it should be replaced with a new one because such repair would detract from the looks and quality of the bumper. In addition, such repair is not considered reasonable in terms of work time.


Repairable Bumpers

1. A bumper with a hole less than 50 mm {1.97 in} in diameter.




YMU980PCM

2. A bumper with a crack less than 100 mm {3.94 in} in length.



YMU980PCN

3. A bumper with a crack less than 100 mm {3.94 in} in length that is less than half of the width of the bumper.




YMU980PCP

BODY STRUCTURE [PLASTIC BODY PARTS]

POLYPROPYLENE BUMPER REPAIR

CHU098050010B02

09-80E




YMU980PCQ

BODY STRUCTURE [PLASTIC BODY PARTS]

PROCEDURE


CHU098050010B03

Repair of polypropylene bumpers having damage that has reached the surface of the polypropylene and are too serious to be restored by painting only.



YMU980PCS

1. Cut the rough edges around the damage with a knife to make it smooth. Sand the area with a sander to make an angle of about 45°.




YMU980PCS

BODY STRUCTURE [PLASTIC BODY PARTS]


2. Weld the damaged area.

- For repair of a cracked area, melt the crack together with a heat gun and a melting attachment.



YMU980PCT


- For repair of a hole, degrease the area on both sides of the bumper and apply aluminium tape on the reverse side of the damage area.



YMU980PCU

09-80E


3. Melt the polypropylene welding rod with a heat gun and deposit it in the cracked area.



YMU980PCV

Note


- Heat the shaded area to melt it.
- Take care not to overly melt welding rod. If the part is welded with the welding rod melted like jelly, the welding strength will be reduced.
- Hold the heat gun 10—20 mm {0.39—0.79 in} from the part being welded.
- Do not move the welding rod until the welded parts cool.



YMU980PCW


BODY STRUCTURE [PLASTIC BODY PARTS]

4. Sand the surface of the polypropylene gradually as it is easily melted by the abrasion heat. Sand the area to which repair agent will be applied.



YMU980PCX

5. Uniformly apply polypropylene primer with a brush to an area larger than the repaired area. Allow to dry about 10 minutes at 20 °C {68 °F}.




YMU980PCY

6. Mix the main agent and the stiffening agent in a ratio of one to one. Apply the mixed repair agent to the damaged area.

Note

- When mixing the main and stiffening agents, take care not to allow bubbles to form.
- The repair agent hardens quickly (about 5 minutes); proceed with the work immediately after mixing the agents.
- Allow about 30 minutes to dry (20 °C {68 °F}) before sanding.



YMU980PCZ

The repair agent is a two part epoxy adhesive.

When the repair agent hardens, it will provide a good finish with the same flexibility as the polypropylenes.


The repair agent for a **urethane** bumper is also a two part adhesive compound. However, this is different from that for a polypropylene bumper. If the incorrect repair agent is used, the repair will be faulty.

BODY STRUCTURE [PLASTIC BODY PARTS]

7. Sand the area with #180—240 sandpaper.

Note

- If excessive force is applied to the area when sanding, the surface will be damaged.
- If fuzz remains around the repaired area, melt it with a heat gun.




YMU980PD0

09-80E

8. Degrease the painted surface.

9. Mix the primer and the hardener at a ratio of one to one. Apply the primer to the repaired area and the surface of the bumper with a brush or spray.



YMU980PD1

Use the primer within 16 hours after it is mixed.


Note

- Polypropylene primer will dissolve even after drying if it is wiped with solvent. Use only water to clean around the primer.

10. Allow the part to dry.

BODY STRUCTURE [PLASTIC BODY PARTS]

11. Add the softener to the urethane primer surfacer and spray it on the repaired area.
 - a. Mixing method
Urethane primer surfacer + Softener Mixture A
Mixture A + hardener Mixture B
Dilute mixture B with thinner to spray on bumper
 - b. Viscosity
14—16 seconds/viscosimeter 20 °C {68 °F}



YMU980PD2

Note

- Mix the solutions at the specified ratio.

- c. Spray pressure
300—400 kPa {3—4 kg/cm², 43—57 psi}
 - d. Standard film thickness
30—40 μ
 - e. Spray method
Spot-spray primer surfacer on bumper three or four times
12. Air drying 20 °C {68 °F} — 8 hours minimum.
Forced drying 60 °C {140 °F} — 1 hour
 13. Lightly sand the complete surface of the bumper with #400—#600 sandpaper. Do not expose the surface of the polypropylene. (Wet or dry sanding is acceptable.)
 14. Wipe the complete surface of the bumper with degreasing agent. Quickly wipe the surface with a clean rag to degrease it.
 15. Apply a matching coat of body color to the polypropylene bumper.

Note

- Be sure to use only urethane primer for a urethane bumper and polypropylene primer for a polypropylene bumper. Other paints for repairing a polypropylene bumper are the same as those for the urethane bumper.

16. Air drying 20 °C {68 °F} — 8 hours minimum.
Forced drying 60 °C {140 °F} — 1 hour

Note

- Let the part air dry when possible as forced drying could cause bubbles in the top coat.