

Seconds (sec)	Equiv. Ratio (AFR)	RPM (RPM)	Calculated Load (%)	Long Term FT (%)	Mass Airflow (g/s)	Short Term FT (%)	Vehicle Speed (mph)	Ign. Tim. Lead. Coil (°)	Ign. Separation (°)
4.84	12.2	7261	97.61	-0.16	246.21	-0.16	55.3	30	15
4.99	12.2	7427	96.43	-0.16	238.95	-0.16	56.54	30	15
5.14	12.35	7545	95.65	-0.16	239.96	-0.16	57.79	30	15
5.32	12.79	7717	95.65	-0.16	259.23	-0.16	59.65	30	15
5.46	12.49	7870	96.04	-0.16	261.37	-0.16	59.65	30	15
5.62	12.2	7995	96.04	-0.16	266.54	-0.16	60.89	30	15
5.81	12.49	8103	95.26	-0.16	264	-0.16	62.14	30	15
6	12.49	8301	93.69	-0.16	271.26	-0.16	62.76	30	14.5
6.14	12.64	8426	92.51	-0.16	280.74	-0.16	64	29.5	13.5
6.37	12.79	8567	91.73	-0.16	266.54	-0.16	65.24	29.5	13.5
6.53	12.2	8770	91.73	-0.16	268.08	-0.16	66.49	29.5	10.5
6.69	11.76	8460	21.17	-0.16	28.31	-0.16	65.87	4.5	-5.5
6.86	12.79	7862	4.31	-0.16	8.48	-0.16	65.24	-5	-15
7	11.47	7245	3.53	-6.4	7.18	-0.16	65.24	17.5	-0.5
7.2	11.17	6826	92.9	-3.28	172.45	-0.16	67.11	29	17
7.34	11.17	6268	97.22	-0.16	156.49	-0.16	67.11	28	11.5
7.5	11.17	6467	99.96	-0.16	182.53	-0.16	68.35	28	15
7.69	11.17	6504	99.57	-0.16	197.22	-0.16	68.35	28	15
7.85	11.17	6620	99.96	-0.16	192.6	-0.16	70.21	28.5	15
8.02	11.17	6666	99.96	-0.16	199.32	-0.16	70.21	28.5	14.5
8.21	11.17	6729	99.96	-0.16	205.19	-0.16	70.84	29	15
8.36	11.17	6811	100.35	-0.16	211.91	-0.16	71.46	29.5	15
8.58	11.17	6918	100.35	-0.16	233.95	-0.16	72.7	30	15
8.75	11.61	6974	100.74	-0.16	242.76	-0.16	73.94	30	15
8.91	11.17	7073	100.35	-0.16	242.69	-0.16	74.56	30	15
9.06	11.32	7096	99.57	-0.16	251.1	-0.16	75.19	30	15
9.23	11.47	7271	98	-0.16	250.01	-0.16	75.81	30	15
9.39	11.17	7243	98	-0.16	233.48	-0.16	76.43	30	15
9.57	11.17	7336	97.22	-0.16	237.46	-0.16	77.05	30	15
9.73	11.17	7431	96.43	-0.16	241.52	-0.16	77.67	30	15
9.91	11.32	7488	96.04	-0.16	245.73	-0.16	78.91	30	15
10.06	11.32	7552	95.65	-0.16	248.38	-0.16	79.54	30	15
10.21	11.32	7607	96.04	-0.16	251.65	-0.16	80.16	30	15
10.37	11.47	7710	96.04	-0.16	243.7	-0.16	80.78	30	15
10.55	11.76	7754	96.04	-0.16	258.64	-0.16	81.4	30	15
10.72	11.47	7862	96.04	-0.16	260.87	-0.16	82.64	30	15
10.91	11.61	7889	96.43	-0.16	263.41	-0.16	83.26	30	15
11.07	11.76	7974	96.43	-0.16	271.76	-0.16	83.88	30	15
11.25	11.61	8042	96.04	-0.16	272.26	-0.16	84.51	30	15

11.42	11.76	8148	95.26	-0.16	271.76	-0.16	85.75	30	15
11.61	11.76	8187	94.86	-0.16	272.26	-0.16	86.37	30	15
11.82	12.05	8275	94.08	-0.16	274.75	-0.16	86.99	30	15
12	11.91	8397	93.3	-0.16	277.25	-0.16	88.23	29.5	14
12.19	12.05	8449	92.51	-0.16	271.76	-0.16	88.86	29.5	14
12.38	11.91	8487	91.73	-0.16	271.76	-0.16	89.48	27	1.5